



H-SERIES (CLASSIC)

Models: Classic 36-2H, Classic 48-2H, Classic 48-4H, Classic 48-6H, Classic 48-2HCX, Classic 48-4HCX

VEHICLE STANDARD FEATURES

Four year limited warranty, two year bumper-to-bumper warranty (less wear items)

Six 6 V (36 V) batteries (Classic 36-2H)

Eight 6 V (48 V) batteries (All other models)

4 hp DC motor (Classic 36-2H)

5.5 hp DC motor (All other models)

300 A controller (Classic 36-2H)

400 A controller (All other models)

Dumping utility box (Classic 48-2HCX, 48-4HCX)

Headlights, taillights, brake lights, turning signals

Folding tinted windshield

Horn and reverse beeper

Rear view mirrors

Battery indicator

Plastic battery box

High/Low speed switch

Automatic battery charger

12 V voltage reducer for accessories

Rear scuff guards

Easy access programming / trouble-shooting port under dash



Classic 36-2H



Classic 48-2H



Classic 48-4H



Classic 48-6H



Classic 48-2HCX



Classic 48-4HCX

VEHICLE OPTIONS AND UPGRADES

LSV (NEV) street legal package (48 V models only)

Custom utility box configurations

Extended roof to cover utility box

Battery filling system

Locking glove box

Black seats

On-board charger

Amber strobe light

Corrosion resistance package

STANDARD COLORS		PREMIUM COLORS	
	Black		Almond Pearl
	Red		Metallic Green
	Navy Blue		Metallic Silver
	White		Yellow



Dumping Utility Box

(Option for Classic 36-2H, Classic 48-2H, Classic 48-4H, and Classic 48-6H)



Enclosed Box



Flat Bed



Stake Box

(Option for Classic 48-2HCX and Classic 48-4HCX)



H-SERIES (CLASSIC)

Vehicle Specifications

Specifications are subject to change without notification.

	Classic 36-2H	Classic 48-2H	Classic 48-4H
DIMENSIONS			
<i>Overall dimensions</i>	115"L x 47"W x 72"H (292 cm x 119 cm x 183 cm)	115"L x 47"W x 72"H (292 cm x 119 cm x 183 cm)	144"L x 47"W x 77"H (366 cm x 119 cm x 196 cm)
<i>Cargo box dimensions</i>	30"L x 43"W x 8.5"H (76 cm x 109 cm x 22 cm)	30"L x 43"W x 8.5"H (76 cm x 109 cm x 22 cm)	30"L x 43"W x 8.5"H (76 cm x 109 cm x 22 cm)
<i>Wheel base</i>	67" (170 cm)	67" (170 cm)	96" (244 cm)
<i>Ground clearance</i>	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)
<i>Wheel type</i>	10" (25.4 cm) aluminum	10" (25.4 cm) aluminum	10" (25.4 cm) aluminum
<i>Tire size</i>	205/50/10, 4-ply DOT	205/50/10, 4-ply DOT	205/50/10, 4-ply DOT
<i>Tire pressure</i>	30 psi (207 kPa)	30 psi (207 kPa)	30 psi (207 kPa)
BODY & CHASSIS			
<i>Chassis</i>	Steel	Steel	Steel
<i>Body material</i>	Plastic	Plastic	Plastic
<i>Roof</i>	Plastic, beige	Plastic, beige	Plastic, body paint match
<i>Side rails</i>	Aluminum	Aluminum	Aluminum
POWER			
<i>Battery system</i>	6x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	4 hp (3 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC
<i>Controller power</i>	300 A Curtis 1243 with regenerative braking	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking
PERFORMANCE			
<i>Passengers</i>	2	2	4
<i>Top speed</i>	18 mph (29 kph)	19.5 mph, 21.9 mph minimum with LSV option (31.4 kph, 35.2 kph minimum with LSV option)	19.5 mph, 21.9 mph minimum with LSV option (31.4 kph, 35.2 kph minimum with LSV option), speedometer included
<i>Top climbing grade</i>	25%	25%	20%
<i>Turning radius</i>	10 ft (3 m)	10 ft (3 m)	12 ft (3.7 m)
<i>Load capacity</i>	650 lbs (295 kg)	650 lbs (295 kg)	960 lbs (435 kg)
<i>Cargo capacity</i>	300 lbs (136 kg)	300 lbs (136 kg)	300 lbs (136 kg)
<i>Weight with batteries</i>	1230 lbs (558 kg)	1230 lbs (558 kg)	1430 lbs (649 kg)
<i>Brake system</i>	Rear drum	Rear drum	Four-wheel hydraulic drum brakes with hand-activated parking brake
<i>Drive train</i>	Direct rear drive with 10.25:1 ratio	Direct rear drive with 10.25:1 ratio	Direct rear drive with 12.49:1 ratio
STEERING AND SUSPENSION			
<i>Steering system</i>	Rack and pinion	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock



H-SERIES (CLASSIC)

Vehicle Specifications

Specifications are subject to change without notification.

	Classic 48-6H	Classic 48-2HCX	Classic 48-4HCX
DIMENSIONS			
<i>Overall dimensions</i>	153"L x 47"W x 77"H (389 cm x 119 cm x 196 cm)	132"L x 47"W x 73"H (335 cm x 119 cm x 185 cm)	162"L x 47"W x 78"H (411 cm x 119 cm x 198 cm)
<i>Cargo box dimensions</i>	30"L x 43"W x 8.5"H (76 cm x 109 cm x 22 cm)	54"L x 43"W x 9.5"H (137 cm x 109 cm x 24 cm)	54"L x 43"W x 9.5"H (137 cm x 109 cm x 24 cm)
<i>Wheel base</i>	125" (318 cm)	96" (244 cm)	125" (318 cm)
<i>Ground clearance</i>	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)
<i>Wheel type</i>	10" (25.4 cm) aluminum	10" (25.4 cm) aluminum	10" (25.4 cm) aluminum
<i>Tire size</i>	20.5x8-10, 6-ply DOT	20.5x8-10, 6-ply DOT	20.5x8-10, 6-ply DOT
<i>Tire pressure</i>	50 psi (345 kPa)	50 psi (345 kPa)	50 psi (345 kPa)
BODY & CHASSIS			
<i>Chassis</i>	Steel	Steel	Steel
<i>Body material</i>	Plastic	Plastic	Plastic
<i>Roof</i>	Plastic, body paint match	Plastic, beige	Plastic, body paint match
<i>Side rails</i>	Aluminum	Aluminum	Aluminum
POWER			
<i>Battery system</i>	8x6 V, Trojan T-105	8x6 V, Trojan T-105	8x6 V, Trojan T-105
<i>Motor power</i>	5.5 hp (4.1 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC	5.5 hp (4.1 kW) Continuous DC
<i>Controller power</i>	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking	400 A Curtis 1268 with regenerative braking
PERFORMANCE			
<i>Passengers</i>	6	2	4
<i>Top speed</i>	19.5 mph, 21.9 mph minimum with LSV option (31.4 kph, 35.2 kph minimum with LSV option), speedometer included	19.5 mph, 21.9 mph minimum with LSV option (31.4 kph, 35.2 kph minimum with LSV option), speedometer included	19.5 mph, 21.9 mph minimum with LSV option (31.4 kph, 35.2 kph minimum with LSV option), speedometer included
<i>Top climbing grade</i>	20%	20%	20%
<i>Turning radius</i>	15 ft (4.6 m)	12 ft (3.7 m)	15 ft (4.6 m)
<i>Load capacity</i>	990 lbs (449 kg)	960 lbs (435 kg)	1290 lbs (585 kg)
<i>Cargo capacity</i>	300 lbs (136 kg)	600 lbs (272 kg)	800 lbs (363 kg)
<i>Weight with batteries</i>	1800 lbs (816 kg)	1500 lbs (680 kg)	1625 lbs (737 kg)
<i>Brake system</i>	Four-wheel hydraulic drum brakes with hand-activated parking brake	Four-wheel hydraulic drum brakes with hand-activated parking brake	Four-wheel hydraulic drum brakes with hand-activated parking brake
<i>Drive train</i>	Direct rear drive with 12.49:1 ratio	Direct rear drive with 12.49:1 ratio	Direct rear drive with 12.49:1 ratio
STEERING AND SUSPENSION			
<i>Steering system</i>	Rack and pinion	Rack and pinion	Rack and pinion
<i>Front suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock
<i>Rear suspension</i>	Leaf spring and shock	Leaf spring and shock	Leaf spring and shock